

DORICA STONE SUPREME IDRA

PELLET THERMOSTOVE



Let yourself be conquered by the veining of the stone, enhance your home with a natural, unique, and sensory material.

Heatable area

203 m².





- 1 - Hygienic floor, in crystal
- 2 - Sliding access for pellet loading
- 3 - Precious soapstone
- 4 - Screen-printed ceramic glass and cast iron firebox door
- 5 - Pelletpower® patented burner
- 6 - Majolica ash-saving floor



TECHNICAL DATA

DIMENSIONS (HXWXD)	1309X560X631
WEIGHT (KG)	246
HEATABLE AREA (M ²)	203
EFFICIENCY UP TO MAX (%)	95,2%
ENERGY CLASS	-
POWER TO THE HEART (KW)	6,8 - 23,7
RATED POWER (KW)	6,5 - 22,5
POWER TO THE WATER (KW)	5 - 19,6
RADIATION (KW)	1,5 - 2,9
HOURLY PELLET CONSUMPTION (KG/H)	1,4 - 4,9
WOOD HOURLY CONSUMPTION (KG/H)V	-
PELLET HOPPER CAPACITY (KG)	30,00
WARM AIR DUCTING	-
MAXIMUM SINGLE DUCTING OUTLET (M)	-
PATENTED BURNER PELLETPOWER®	SI
ROMM VENTILATION	-
PRIMARY AIR FROM OUTSIDE	SI
CO EMISSIONS (MG/M ³ ; 13% DI O ₂)	86
CO EMISSIONS (MG/M ³ ; 10% DI O ₂)	-
DUST EMISSIONS (MG/M ³ ; 13% DI O ₂)	18,7
DUST EMISSIONS (MG/M ³ ; 10% DI O ₂)	-
SILENCE(DB)	36,00
REMOTE CONTROL	-
RADIO CONTROL WITH ROOM TEMPERATURE THERMOSTAT	-
WEEKLY PROGRAMMER (3 DAILY LIGHTING)	SI
SMART INFO FUNCTION	SI
SYSTEM CIRCULATING PUMP	SI
EXPANSION TANK	SI
OVER PRESSURE VALVE	SI

FLUE GASEXHAUST DIAMETER (MM)	100
MIN. FLUE DRAUGHT PRESSURE (PA)	10
ELECTRIC CONSUMPTION (WATT)	90-340
HIGH TEMPERATURE SAFETY THERMOSTAT	SI

THERMOROSSI S.p.A.

Via Grumolo, 4 | 36011 Arsiero (VI) | Italy | E-mail: info@thermorossi.it

Tel: 800.44.88.77 | Fax: 0445 741657 | P.IVA 00168470243 | Iscr. REA99797 Vicenza | Cap. Sociale di 156,000,00 l.v.