

BELLAVISTA R2 SILENT

PELLET STOVE



Innovation: it means to simplify an operation hard to do. Comfort: it is the way to improve the quality of living in the home. Safety: it means to take care of the environment and those who use our products. Design: it means to study the form and technological solutions to ensure we are always one-step ahead. Research and Development: it means to take all this and combine together in one unique project. Look far. Designed from a new point of view: yours. Pellet Stove available also with different technology in Silent, Air or Plus version.

Heatable area

81 m².





- 1 - Upper smoke exhaust
- 2 - Hygienic, glass top with food warmer function
- 3 - Patented heat exchanger with Thermocore® technology
- 4 - Firebox with 270° fire view
- 5 - Finishing with decorative stones
- 6 - PelletPower® patented burner



TECHNICAL DATA

DIMENSIONS (HXWXD)	1493X481X671
WEIGHT (KG)	183
HEATABLE AREA (M²)	81
EFFICIENCY UP TO MAX (%)	85,4%
ENERGY CLASS	A+
POWER TO THE HEART (KW)	3,9 - 10,5
RATED POWER (KW)	3,3 - 9
POWER TO THE WATER (KW)	-
RADIATION (KW)	-
HOURLY PELLET CONSUMPTION (KG/H)	0,8 - 2,2
WOOD HOURLY CONSUMPTION (KG/H)V	-
PELLET HOPPER CAPACITY (KG)	25,00
WARM AIR DUCTING	OPT
MAXIMUM SINGLE DUCTING OUTLET (M)	OPT
PATENTED BURNER PELLETPOWER®	SI
ROMM VENTILATION	OPT
PRIMARY AIR FROM OUTSIDE	SI
CO EMISSIONS (MG/M³; 13% DI O2)	65
CO EMISSIONS (MG/M³; 10% DI O2)	-
DUST EMISSIONS (MG/M³; 13% DI O2)	14,2
DUST EMISSIONS (MG/M³; 10% DI O2)	-
SILENCE(DB)	-
REMOTE CONTROL	SI
RADIO CONTROL WITH ROOM TEMPERATURE THERMOSTAT	OPT

WEEKLY PROGRAMMER (3 DAILY LIGHTING)	SI
SMART INFO FUNCTION	SI
SYSTEM CIRCULATING PUMP	-
EXPANSION TANK	-
OVER PRESSURE VALVE	SI
FLUE GASEXHAUST DIAMETER (MM)	100
MIN. FLUE DRAUGHT PRESSURE (PA)	12
ELECTRIC CONSUMPTION (WATT)	60-320
HIGH TEMPERATURE SAFETY THERMOSTAT	SI

THERMOROSSI S.p.A.

Via Grumolo, 4 | 36011 Arsiero (VI) | Italy | E-mail: info@thermorossi.it

Tel: 800.44.88.77 | Fax: 0445 741657 | P.IVA 00168470243 | Iscr. REA99797 Vicenza | Cap. Sociale di 156,000,00 I.v.